




Lite Series



L x W x H = 22.5" x 7" x 1"

Watts	Lumens	lm/W	
18	2,200	122.0	

Footcandle Plot @ 9 ft



Description

Carson's 18W 2' LED U-bend T8 tube bypasses the ballast and saves 44% in energy costs when compared to F32 fluorescent tubes. Available in two color temperatures, the single side powered G13 bi-pins retrofit into unshunted lampholders that run directly off line voltage. Ideal for offices, warehouses, and parking garages.

18W 2' U-Bend T8 Tube

Bypass Ballast

Key Features

- Uses Epistar SMD2835 chip
- •Rated for 50,000 hours
- •5 year warranty
- •UL listing: E472081
- •DLC Qualified Product List (Model #: T8U-IDFH11-2100)
- •Color Rendering Index: 82
- Total Harmonic Distortion: 20%
- •Power Factor: 0.9
- Input voltage: AC 110V-277V
- •LED quantity: 120 chips
- Built-in internal driver bypass external ballast
- •Single side powered bi-pin energizes unshunted lampholder
- Frosted glass tube enables maximum light diffusion
- •Annual Savings of \$8.58

Calculations are based on 4,380 annual hours of operation and \$0.14 average cost per kWh

Ordering Information: CL-BPT8U218N

CL	BP	T8U	2	18	Ν
Line	Туре	Shape	Length	Watts	Color
CL - Lite	BP - Bypass Ballast	T8U - U-Bend	2 - 2 feet	18 - 18 Watts	C - 4000K
					N - 5000K